

H-125 SERIES™

WATER CONDITIONING SYSTEM



- Agriculture
- Apartment Buildings
- Boiler Water Treatment
- Car Washes
- Commercial Buildings
- Condominiums
- Dairies
- Factories
- Hospitals
- Homes
- Laundries
- Mobile Home Parks
- Motels and Hotels
- Nursing and Rest Homes
- Office Buildings
- Restaurants
- Schools

The H125 Control is User Friendly and Reliable.

- Modular Design
- Non-Corrosive Valve Body & Internals
- One Piece Stack Assembly
- Piston Operated
- No Nuts, Bolts or Screws
- Disassemble and Reassemble in Minutes

**Hellenbrand®**

H-125 SERIES™

WATER CONDITIONING SYSTEM



Going Green

Brine Reclaim – The H125 standard electronic package is capable of reclaiming up to 30% of the salt used in regeneration for the next regeneration. Salt savings will vary depending on the lbs. of salt per cubic foot of resin used to regenerate.

Water Reclaim – The H125 standard electronic package is capable of reclaiming much of the water used to regenerate the water softener and re-use that water to flush toilets. This water is typically soft and is free of the salt/brine discharge which is diverted to your standard drain/waste system. A holding tank is installed to reclaim this water, along with a re-pressurization and disinfection system. A separate line is required to re-fill this tank when the reclaim water drops below a certain level between regenerations.



H125 Features and Benefits

- 1.25" internal porting, provides higher service flows with less pressure drop
- 12-Volt Operation AC or DC
- Electronic Meter Demand with Calendar Day Override
- Scrolling User Screen shows capacity remaining, time of day and flow rate
- 12-Volt Relay Driver allows multiple dry contact signals
- Service Interval Screen displays preventative maintenance reminder
- Differential Pressure Switch Capability
- Fully Programmable Cycle Position and Times
- Nine Cycle Control
- Soft Water Brine Tank Re-Fill
- Multiple Backwash and Rinse Capabilities
- Quiet Operation
- Variable Reserve automatically adjusts to changing water usage patterns.
- Several programming options including: variable reserve, fixed reserve, calendar day override, delayed or immediate regeneration.
- Diagnostics
 - Days since last regeneration
 - Gallons since last regeneration
 - Gallon reserve capacity last 7 days
 - 63 Days history of daily totals usage
 - Maximum flow rate for the last seven days
 - Total number of regenerations
 - Total days in service
 - Total gallons processed
- Permanent memory backup of all programming
- 2-1/2 years Time of Day Backup
- Uses less than \$2 of electricity per year

System Designs Options

Single, Twin Parallel,
Twin Alternating
Brine Reclaim
No Raw Water Bypass
Separate Source Regeneration

Meter Accuracy

Model: H125
Flow Ranges 0.25-34 GPM
Accuracy: ±5%

Specifications

HELLENBRAND WARRANTY
Go to www.hellenbrand.com for full details.

DEMAND MODEL NAME	MINERAL CU. FT.	LOW SALT GRAINS/LBS.	CAPACITY MED. SALT GRAINS/LBS.	HIGH SALT GRAINS/LBS.	FLOW RATE @ 15 PSI	PEAK FLOW RATE @ 25 PSI	BACK WASH RATE GPM	MINERAL TANK (INCHES)	BRINE TANK ¹	
									TANK SIZE (INCHES)	SALT STORAGE (POUNDS)
H125-32-10ED	1	19,000/6	28,000/10	32,000/15	22	31	2.2	1044	18x40	330
H125-48ED	1.5	28,500/9	42,000/15	48,000/22.5	19	28	2.2	1054	18x40	330
H125-64ED	2	38,000/12	56,000/20	64,000/30	25	34	4.2	1354	18x40	330
H125-96ED	3	57,000/18	84,000/30	96,000/45	24	33	4.2	1465	18x40	300
H125-128ED	4	76,000/24	112,000/40	128,000/60	25	34	5.3	1665	24x41	640
H125-160ED	5	95,000/30	140,000/50	160,000/75	27	35	7.5	1865	24x50	750
H125-192ED	6	114,000/36	168,000/60	192,000/90	26	34	7.5	1865	24x50	750

¹Suggested brine tank size with grid plate option.



Hellenbrand, Inc.
1-800-626-1417
www.hellenbrand.com



DEALER NAME: