

Specifications

HELLENBRAND WARRANTY

Go to www.hellenbrand.com for full details.

DEMAND MODEL NAME	MINERAL CU. FT.	LOW SALT GRAINS/LBS.	CAPACITY MED. SALT GRAINS/LBS.	HIGH SALT GRAINS/LBS.	FLOW RATE @ 15 PSI	PEAK FLOW RATE @ 25 PSI	BACK WASH RATE GPM	MINERAL TANK (INCHES)	BRINE TANK ¹	
									TANK SIZE (INCHES)	SALT STORAGE (POUNDS)
H125-32-10ED	1	19,000/6	28,000/10	32,000/15	22	31	2.2	1044	18x40	330
H125-48ED	1.5	28,500/9	42,000/15	48,000/22.5	19	28	2.2	1054	18x40	330
H125-64ED	2	38,000/12	56,000/20	64,000/30	25	34	4.2	1354	18x40	330
H125-96ED	3	57,000/18	84,000/30	96,000/45	24	33	4.2	1465	18x40	300
H125-128ED	4	76,000/24	112,000/40	128,000/60	25	34	5.3	1665	24x41	640
H125-160ED	5	95,000/30	140,000/50	160,000/75	27	35	7.5	1865	24x50	750
H125-192ED	6	114,000/36	168,000/60	192,000/90	26	34	7.5	1865	24x50	750

¹Suggested brine tank size with grid plate option.