

# Specifications

## HELLENBRAND WARRANTY

Go to [www.hellenbrand.com](http://www.hellenbrand.com) for full details.

DEMAND MODEL NAME	MINERAL CU. FT.	LOW SALT GRAINS/LBS.	CAPACITY MED. SALT GRAINS/LBS.	HIGH SALT GRAINS/LBS.	FLOW RATE @ 15 PSI	PEAK FLOW RATE @ 25 PSI	BACK WASH RATE GPM	MINERAL TANK (INCHES)	BRINE TANK <sup>1</sup>	
									TANK SIZE (INCHES)	SALT STORAGE (POUNDS)
H300-300	10	190,000/60	280,000/100	320,000/150	98	126	12	24x72	30x50	1110
H300-300-30	10	190,000/60	280,000/100	320,000/150	158	205	20	30x72	30x50	1110
H300-450	15	285,000/90	420,000/150	480,000/225	144	186	20	30x72	39x48	2030
H300-600	20	380,000/120	560,000/200	640,000/300	172	222	30	36x72	39x48	1640
H300-750	25	475,000/150	700,000/250	800,000/375	190	244	40	42x72	42x60	2580
H300-900	30	570,000/180	840,000/300	960,000/450	180	238	40	42x72	50x60	4130
H300-1200	40	760,000/240	1,120,000/400	1,280,000/600	194	251	50	48x72	50x60	4130
H300-1500	50	950,000/300	1,400,000/500	1,600,000/750	200	260	65	54x72*	60x64	4000
H300-1950	65	1,235,000/390	1,820,000/650	2,080,000/975	205	260	80	60x72*	72x45	4800
H300-2100	70	1,330,000/420	1,960,000/700	2,240,000/1,050	210	270	90	63x86	72x54	4800

Mineral tank sizes shown are with polyglass tanks. (\* denotes steel tanks)

Product improvement designs are subject to change without notice.

Refer to Hellenbrand Bulletin 2050 "Flow Rates and Soft Water Quality (Hardness Leakage)" if your application requires that levels of hardness leakage do not exceed "x".